



HK802



- Special tread compound design for lower heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.
- Three ribs with horizontal lines on the shoulder optimize speed and traction performance, gives excellent performance on wet road.

TYRE SIZE	PLY RATING	TREAD PATTERN	TREAD DEPTH (MM)	RIM SIZE	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	Design New Tyre(mm)		Inflation Pressure(kPa)		Load Capacity(kg)	
								OUTER DIAMETER	SECTION WIDTH	SINGLE	DUAL	SINGLE	DUAL
7.00R16LT	12PR	HK802	10.5	5.50F	TT	115/110	L	775	200	670	670	1215	1060
	14PR					118/114				770	770	1320	1180
7.50R16LT	12PR	HK802	13.5	6.00G	TT	120/116	L	805	215	670	670	1400	1250
	14PR					122/118				770	770	1500	1320
8.25R16LT	14PR	HK802	14.5	6.50H	TT	126/122	L	855	235	670	670	1700	1500
	16PR					128/124				770	770	1800	1600
8.25R20	14PR	HK802	15.0	6.5	TT	136/134	K	974	236	830	830	2240	2120
	16PR					139/137				930	930	2430	2300
9.00R20	14PR	HK802	15.5	7.0	TT	141/139	K	1019	259	790	790	2575	2430
	16PR					144/142				900	900	2800	2650
10.00R20	16PR	HK802	16.0	7.5	TT	146/143	K	1054	278	830	830	3000	2750
	18PR					149/146				930	930	3250	3000
11.00R20	16PR	HK802	15.5	8.0	TT	150/147	K	1085	293	830	830	3350	3075
	18PR					152/149				930	930	3550	3250
12.00R20	18PR	HK802	16	8.5	TT	154/151	K	1125	315	830	830	3750	3450
	20PR					156/153				930	930	4000	3650
11R22.5	14PR	HK802	17.5	8.25	TL	144/142	M	1054	279	720	720	2800	2650
	16PR					146/143				830	830	3000	2725
315/80R22.5	16PR	HK802	17.5	9.0	TL	151/148	M	1076	312	760	760	3450	3150
	18PR					154/151				830	830	3750	3450
	20PR					156/150	L			850	850	4000	3350
	22PR					167/164				950	950	5450	5000
	22PR					167				C	950	950	-
12.00R24	18PR	HK802	16.0	8.5	TT	158/155	K	1226	315	830	830	4250	3875
	20PR					160/157				930	930	4500	4125
205/85R16LT	14PR	HK802	10.5	6J	TL	117/115	L	775	200	575	575	1285	1215